

RECESSED BAB R

CORRECTIONAL
GRADE EXIT SIGN
WITH ROUNDED
DOOR FACING



Our **BAB (R)** is a heavy duty, vandal resistant, Ligature Resistant Recessed LED exit sign designed for high-performance and long-life. This is the perfect EXIT SIGN solution for correctional and/or behavioral health facilities, schools, and any public area where strength and safety is paramount. A .125" clear polycarbonate lens is sealed to the doorframe for added safety.

CONSTRUCTION: One-piece construction made from cold roll steel or stainless steel. Doorframe to match housing construction. Corners continuously seam welded and smooth.

FASTENERS: Tamper Proof T25 Torx with center pin reject is standard. Allen head fasteners available as an option.

LEGEND: Legend illuminated by internal high output LEDs. Lettering 6.0" high with .75" stroke. Internal panels with stencil cut letters and red or green filter panel. A .125" clear polycarbonate lens is standard. EZ snap-out chevron directional indicators.

ELECTRICAL: Features 624 nm Red or 527 nm Green LED light sources.

FINISH: TGIC white polyester powder coat with a 5-stage pre-treatment. Salt spray test of over 1,000 hours. Reflectance of 92%. See options for black exterior. Stainless steel doorframe construction and finishes available.

LISTINGS: ETL and cETL listed for Wet Location. Meets or exceeds UL924 and NFPA 101 Standards. Meets or exceeds CSA and NRCAN requirements. IK10 rated. BAA and BABA compliant.

OPTIONS: Available with a sealed nickel-cadmium emergency battery pack with standard deep cycle battery conditioning. Emergency battery provides up to 90 minutes of emergency operation. Emergency Battery Pack (EMB) suitable for 10°C to 45°C (50°F to 113°F). SELF-DIAGNOSTIC (SDT) is standard. A Wet Location option is also available (only available as Self-Diagnostic).

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty

Ordering Info Next Page ►

Ordering Example: BAB-R-B14-R-M-SDT

BAB	R			
SERIES	MOUNTING	HOUSING	LEGEND COLOR	FASTENERS
BAB	R Recessed	B12 Cold Roll 12 Gauge Steel (Painted) B14 Cold Roll 14 Gauge Steel (Painted) B16 Cold Roll 16 Gauge Steel (Painted) B18 Cold Roll 18 Gauge Steel (Painted) SH14 Stainless Steel 14 Gauge (Painted) SH14B Stainless Steel 14 Gauge (Brushed) SH16 Stainless Steel 16 Gauge (Painted) SH16B Stainless Steel 16 Gauge (Brushed) SH18 Stainless Steel 18 Gauge (Painted) SH18B Stainless Steel 18 Gauge (Brushed)	G Green R Red	AH Allen Head w/ Center Pin
Consult factory for any gauge not listed.				

	VOLTAGE	OPTIONS
M	Multi-Volt (120-277V)	BLANK AC Only EMB Emergency Backup (90 minutes) BLK Black Exterior (N/A with stainless steel doorframe material) TS Torx Screwdriver BE Black Exit sign insert WL Wet Location (1) AAS Auxiliary AC Supply (Matches Voltage Selection) ADC Auxiliary DC Supply (6-24 Volts) LRC Ligature-resistant caulk



(1) Wet location only available as self-diagnostic. From door to housing only, recessed body is damp location only.

ELECTRICAL INFORMATION	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
RED SDT	2.5	2.5	0.05	0.05
GREEN DT	2.7	2.7	0.05	0.05

Dimensions on Next Page 

DIMENSIONS

