

TOP, SIDE OR SURFACE MOUNT

BAB-U

UNIVERSAL
PRISON GRADE
LED EXIT SIGN



STATE OF NEW YORK COMPLIANT
Office of Mental Health (OMH)



TOP MOUNT EXAMPLE



SEE OUR **BABT** FOR AN LIGATURE-RESISTANT EXIT SIGN

The **BAB (U)** is a Universal, correctional grade LED exit sign. Perfect for any application that requires a heavy duty, vandal resistant exit sign. This fixture can be mounted either top, side or surface mount, and is available as a single or double sided fixture. This is a clean and attractive exit sign designed to last.

HOUSING: Constructed from die formed from US sourced cold rolled steel in a variety of gauges (see ordering information for options).

DOOR: One-piece die-formed cold rolled steel as specified in options. Corners continuously seam welded and smooth with no post grinding (TIG).

FASTENERS: Tamper Proof T25 Torx with center pin reject is standard. Allen head fasteners available as an option.

FINISH: TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. See Options for black exterior.

LEGEND: Legend illuminated by internal high output LEDs. Lettering is 6.0" high with .75" stroke (meeting most requirements). A .125" clear polycarbonate lens is standard. EZ snap-out chevron directional indicators.

ELECTRICAL: 624 nm Red or 527 nm Green LED light sources.

OPTIONS: 1.2V Long life, maintenance-free, rechargeable NiCd battery is available as an option. Emergency battery provides up to 90 minutes of emergency operation. Emergency Battery Pack (EMB) suitable for 10°C to 45°C (50°F to 113°F).

LISTINGS: ETL and cETL listed. Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for damp locations (0°C – 50°C). Certified to CEC under Title 20 Regulations. BAA and BABA compliant. Also compliant with the State of New York OMH Regulations.

WARRANTY: 5 - Year Limited Warranty. Complete warranty and terms located at: www.aelnow.com/warranty.


Ordering Info Next Page ►



ORDERING INFORMATION EXAMPLE: BAB-U-1-B14-R-M-SDT

BAB	U			
SERIES	MOUNTING	FACE	HOUSING / DOOR MATERIAL	LEGEND COLOR
BAB	U Universal (top, side or surface mount)	1 Single Face 2 Double Face	B12 Cold Roll 12 Gauge Steel (Painted) B14 Cold Roll 14 Gauge Steel (Painted) B16 Cold Roll 16 Gauge Steel (Painted) B18 Cold Roll 18 Gauge Steel (Painted) SH14 Stainless Steel 14 Gauge (Painted) SH14B Stainless Steel 14 Gauge (Brushed) SH16 Stainless Steel 16 Gauge (Painted) SH16B Stainless Steel 16 Gauge (Brushed) SH18 Stainless Steel 18 Gauge (Painted) SH18B Stainless Steel 18 Gauge (Brushed) <i>Consult factory for any gauge not listed.</i>	G Green R Red

VOLTAGE	FASTENERS	OPTIONS	
M 120/277VAC	AHC Allen Head w/ Center Pin Reject	BLANK AC Only EMB Emergency Backup (90 minutes) BLK Black Exterior (N/A with stainless steel doorframe material) TS Torx Screwdriver BE Black Exit sign insert SDT Self-Diagnostic Testing AAS Auxiliary AC Supply (Matches Voltage Selection) ADC Auxiliary DC Supply (6-24 Volts)	



**ALLENHEAD WRENCH INCLUDED FOR
MANUAL PUSHING TEST BUTTON
(if applicable)**

ELECTRICAL INFORMATION

	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
RED SDT	2.5	2.5	0.05	0.05
GREEN DT	2.7	2.7	0.05	0.05

Dimensions on Next Page ►



DIMENSIONS

