



CATALOG #:

PROJECT:

TYPE:







The **BAM** Series is a High Abuse LED Surface Mount fixture designed applications that require a fixture with a high level of vandal resistance. High performance linear configured LED module boards. The BAM Series of LED Fixtures were designed to be high quality, energy efficient LED fixtures for use in commercial applications, correctional facilities, institutions, schools, shopping centers and other public buildings.

CONSTRUCTION: The fixture is constructed of heavy gauge cold rolled steel body. Drill points for maximum security. Integral locking lugs opposite the retention screws. Provided with stainless steel screws. Optional tamper proof torque screws available (see options). Neoprene gasket eliminates dust, prevents moisture and insects from penetrating. The housing is 2" in height. Surface Mount. There are 7/8" K/O in both ends, and across the back of the housing for multiple mounting options. Will accept ½" conduit in either, and or both ends.

FINISH: White polyester polymer finish with a high reflectivity. Injection molded prismatic polycarbonate lens with UV inhibitors.

ELECTRICAL SYSTEM: Electronic drivers are available for 120/277V applications. Long-life LED system rated for 100K life hours (L70 @ 25°C). Metal gear tray for internal LED driver. Complies with federal energy efficiency standards.

LISTINGS: ETL and cETL listed for damp locations.

MOUNTING: The fixture can be surface mounted

LED: 80 CRI or 90 CRI LEDs available in 3000K, 3500K, 4000K, 5000K, Red, Blue, and Amber.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at: www.aelnow.com/warranty

Ordering Information on Next Page











CATALOG #:

PROJECT:

TYPE:

ORDERING INFORMATION:

Example: BAM-4-40-8L-M

SERIES	SIZE	ССТ	OUTPUT	VOLTAGE	OPTIONS
BAM	4 4'	30 3000K 35 3500K	4L 4000 Lumens (Standard) 5L 5000 Lumens (Medium) 8L 8000 Lumens (High)	M 120/277V	BLANK 0-10V 1% Dimming Driver (included standard)
		40 4000K			14EBL 14 Watt Emergency Ballast
		50 5000K			STP Stainless Steel Tamper-Proof Screws
					90 90 CRI





