

CNXU

LED NEMA4X/
NSF EXIT SIGN



Our **CNXU** is a durable, high-impact and tamper-proof LED exit sign. Perfect for any application that requires a vandal resistant exit sign. Also features ultra bright, energy efficient, and long life Red or Green LEDs.

ELECTRICAL: Dual 120/277 voltage. Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check-battery). Charge rate/power "ON" LED indicator light and magnetic test switch for mandated code compliance testing. 4.8V long-life, maintenance-free, rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

LISTINGS: Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes. IP66 rated for Ingress protection. NEMA4X and NSF rated. Certified to CEC under Title 20 Regulations. UL certified for use in food service operations and for wet locations (-20°C – 50°C).

MOUNTING: Universal knockout pattern on back provided with gasket for watertight seal for back mount. Polycarbonate mounting canopy included for top or end mount.

HOUSING: Housing is reinforced polycarbonate construction in white or black finish. Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws. Knockouts provided for conduit feed applications. EZ snap-out Chevron directional indicators.

DOOR: One-piece die-formed prime grade 14-gauge. Corners continuously seam welded and smooth with no post grinding (TIG).

FINISH: TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. See Options for black exterior.

OPTIONS: SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes. 2C-120V/2C-277V: Voltage-specific dual circuit option on the AC-only unit enables it to be connected to two different supplies at the same time. Tamper-proof hardware helps discourage unauthorized access to the unit.

WARRANTY: 5 - Year Limited Warranty. Batteries prorated for five years. Complete warranty and terms located at: www.aelnow.com/warranty.

Ordering Information on Next Page ►

ORDERING INFORMATION: EXAMPLE: CNXU-G-W-EM-TP

SERIES	NO. OF FACES	LETTER COLOR	HOUSING COLOR	BATTERY	OPTIONS
CNXU	1 Single Face 2 Double Face	G Green R Red	W White B Black	BLANK AC-Only EM EM NiCd Battery	SDT Self-Diagnostics* 2C-120 Dual Circuit With 120V Input** 2C-277 Dual Circuit With 277V Input** TP Tamper-Proof
Best # INDWLEZU					

*Available in EM units only.

**Not available with EM units

DIMENSIONS

