



CATALOG #:  
PROJECT:  
TYPE:

# EM22-16BAA

## P-LED SEMI-RECESSED LED MR-16 EMERGENCY UNIT



**ILLUMINATION:**

Two fully adjustable semi-recessed, round 7-watts LED MR16 lamp heads for optimal light distribution Ultra-bright, energy efficient, long-life White LED lamps provide up to 76-ft center-to-center spacing with 3-ft path of egress at 7.5-ft mounting height.

**ELECTRICAL:**

Dual 120/277 voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. LVD (low voltage disconnect) prevents battery from deep discharge. 6V maintenance-free, rechargeable sealed lead acid battery. Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

**MOUNTING:** Universal knockout pattern on the backplate for wall mount. Snaps into place making internal electrical connections. Knockout for conduit applications. Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

**OPTIONS :**

BAA compliant.  
SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.

**WARRANTY/LISTING :**

- Five year warranty on all electronics and housing. Battery pro rated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (20°C – 40°C).

**ORDERING INFORMATION Example: EM2216-B-BAA**

SERIES	HOUSING COLOR	LAMP	OPTION
EM2216	Blank White B Black	PLED 7.0W High Lumen White LED Lamps standard	BAA BAA Compliant PLED 5.0W High Lumen White LED Lamps SDT Self-diagnostics



*Special voltage options available. Check with your Representative.*

Best#RMR-16BAA

## DIMENSIONS

