

OVER-THE-BED  
**F558**  
LUMINAIRE



The F558 is a specification grade wall mount for “over-the-bed” applications and may also be used in bath, stairwells and offices. Its rectangular shape provides a clean, crisp profile.

**HOUSING:** Housing is die-formed and embossed code 22 gauge steel. Standard finish is high reflectance baked white enamel; custom finishes are available as an option. Wiring knockouts are provided on back of housing. The clear, ribbed lens is fully captured by the end plate. End cap is held in place with acorn nuts.

**ELECTRICAL:** All units are furnished with UL Listed Class P thermally protected driver. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648.

**MOUNTING:** Unit is equipped with holes and 7/8” knockouts in housing for surface mounting. Fixture may be mounted individually or with optional joiner bands may be used in a continuous run.

**FEATURES/OPTIONS:**

- Optional dividers, front baffles and dual drivers
- Clean, crisp profile
- Up and down light are individually controlled.
- Minimum CRI 82

**LISTINGS:** UL Certified for damp locations.

**WARRANTY:** 5-Year Limited Warranty. Complete warranty and terms located at [www.aelnow.com/warranty](http://www.aelnow.com/warranty)

Ordering Information on Next Page ►

## Ordering Example: F558-4-4K-8960-EMB

| SERIES | SIZE     | CCT       | ILLUMINATION <sup>(1)</sup> | OPTIONS                         |
|--------|----------|-----------|-----------------------------|---------------------------------|
| F558   | 2 2 Feet | 3K 3000K  | 3166 (17W)                  | EMB Emergency ballast           |
|        | 3 3 Feet | 35K 3500K | 4350 (24W)                  | REFS Silver Reflector           |
|        | 4 4 Feet | 4K 4000K  | 5470 (31W)                  | OCC-E External Occupancy Sensor |
|        |          | 5K 5000K  | 6452 (39W)                  | BI-LEV Bi-level dimming system  |
|        |          |           | 3159 (20W)                  | O Grounded outlet               |
|        |          |           | 4480 (30W)                  | TOG Toggle Switch               |
|        |          |           | 5684 (42W)                  | PULL Pull chain switch          |
|        |          |           | 6318 (40W)                  | NL Night Light                  |
|        |          |           | 8960 (60W)                  | 3WAY 3 way system               |
|        |          |           | 11368 (84W)                 | BF Center baffle                |
|        |          |           |                             | PRIS Prismatic lens             |
|        |          |           |                             | DL Down light only              |
|        |          |           |                             | POLY Polycarb lens              |
|        |          |           |                             | FR Frosted lens over LED boards |

NOTES: 0-10v low voltage dimming standard per fixture (1) Higher and custom lumen packages available upon request. Inquire with factory for lumen options of 18" and 36" models.

## DIMENSIONS

