

WALL/SURFACE MOUNT

FL55

LUMINAIRE



This covered wall unit, our FL55 is designed to provide maximum lumen output in areas such as hallways, bathrooms, kitchens, stairways, and hospitals. An assortment of options in either single or double lamp allows this utility wall and surface mounted unit to satisfy a variety of lighting needs.

HOUSING: Housing is designed from heavy gauge die formed steel and finished in either baked white enamel or polyester powder coating. Socket plate is riveted to housing adding to the structural support of the fixture. Durable LED Acrylic lens. End plates are attached by acorn nuts and secure the lens to the fixture.

ELECTRICAL: All units are furnished with UL Listed Class P thermally protected ballast. Other voltages are available upon request. Fixtures meet requirements for UL Luminaire Standard # 1598. All units comply with National Energy Standard. All units are UL certified damp location M 59006648.

MOUNTING: Unit is equipped with holes and 7/8" knockouts in housing for surface mounting. Fixture may be mounted individually or with optional joiner bands may be used in a continuous run.

LISTINGS: UL Certified for damp locations.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty

Ordering Information on Next Page ►

Ordering Example: FL55-2-3K-5470-NL

SERIES	SIZE	CCT	ILLUMINATION ⁽¹⁾	OPTIONS
FL55	2 2 Feet 4 4 Feet	3K 3000K 35K 3500K 4K 4000K 5K 5000K	 3166 (17W) 4350 (24W) 5470 (31W) 6452 (39W) 3159 (20W) 4480 (30W) 5684 (42W) 6318 (40W) 8960 (60W) 11368 (84W)	EMB Emergency Battery OCCE External Occupancy Sensor OCCI Internal Occupancy sensor BILEV Bi-level dimming system O Grounded outlet TOG Toggle Switch PULL Pull chain switch NL Night Light

NOTES: 0-10v low voltage dimming standard per fixture (1) Higher and custom lumen packages available upon request. Inquire with factory for lumen options of 18" and 36" models.

DIMENSIONS



•24" 46" 48" Standard Lengths (X)
(or custom lengths available upon request)

