

RBUFO

UFO HEAD BOLLARD

Lumen and CCT Selectable

1700 to 3000 Lumens

3000 to 5000K CCT



Model #	L (in)	W (in)	B (in)	H (in)	Weight (lbs)
BOL-UFO-302317L-3CCT	9.76	9.76	6.3	42.25	13.22



The RBUFO is an attractive bollard that features user selectable CCT (3000k-warm white 4000k-neutral white, and 5000k-cool white), a choice between black and bronze finishes, and selectable lumens.

CONSTRUCTION: Premium powder-coat, aluminum, dark bronze or black housing.

FLEXIBILITY: Field selectable 3000k(warm white), 4000k (neutral white) and 5000k (cool white) color temperatures. Tri-lumen selectable delivers 1,700 to 3,000 nominal lumens.

ELECTRICAL: Operating temperature (ambient): -40°C to 60°C (-40°F to 140°F). Universal 120-277V AC voltage (50-60Hz) is standard. 0-10VDC dimming drivers are standard. Input transient surge protection = 4kV. Power factor > 0.90. Total Harmonic distortion < 20%. Long-life LEDs provide 192,000 hours of operation with at least 70% of initial lumen output (L70), and 58,000 hours with at least 90% of initial lumen output (L90).

WARRANTY & LISTINGS: cULus listed for wet locations in ambient temperatures from -40°C to 55°C (-40°F to 131°F). IP65 rated for ingress protection. IK10 rated for impact protection. 5-year warranty of all electronics and housing.

ORDERING INFORMATION. Example: RBUFO-BLK

SERIES	CCT/LUMENS	HOUSING FINISH
RBUFO	User Selectable	Blank Dark Bronze BLK Black

