

SB400W

400W LED SHOE BOX



Our Area Light/Shoebox Series is the best option to replace 100W to 1000W metal halide luminaires. The slim profile design delivers maximum efficiency. A wide range of lumen packages for any type of applications. With extensive selection of accessories, including photocell receptacles, motion sensor, mountings and finish colors. Ideal for commercial parking lots, car dealership, walk ways, street lighting, and places where much needed light.

FEATURES

- Lumileds LED, high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V/AC 277-480V.
- Die-cast aluminum cooling design, high quality and better cooling for LED Tj < 85°C.
- Excellent optics design, greatly improve the light utilization and evenness.
- Motion sensor control available (Optional)



SPECIFICATION

WATTAGE	400W
LUMEN	56783 lm
EFFICACY	141 lm/W
CCT	5000K
CRI	70
INPUT VOLTAGE	AC120-277V / AC277-480V
DISTRIBUTION	Type II, Type III, Type IV, Type V
POWER FACTOR	0.95
DRIVER EFFICACY	90%
DIMMING	0-10Vdc
LIFE SPAN	over 50,000 hrs
WORKING TEMPERATURE	-22°F ~ 113°F
STORAGE TEMPERATURE	-40°F ~ 176°F
OUTDOOR RATING	Wet location / IP65
CABLE	3 core, 18AWG 0.5m
WARRANTY	5 year limited


ORDERING EXAMPLE: **SB-40W-27-50K-S-TN-U-Y-M**

PRODUCT	WATTAGE	VOLTAGE	CCT	FINISH	DISTRIBUTION	MOUNTING	CONTROL 1	CONTROL 2
SB (Shoebox)	40W - (400W)	27 (AC120-277V) 48 (AC277-480V)	40K - (4000K) 50K - (5000K)	D - (Dark Bronze) W - (White) B - (Black) S - (Silver)	T2 - (Type II) T3 - (Type III) T4 - (Type IV) T5 - (Type V)	S - (Slipfitter) A - (Arm) T - (Trunnion)	P - (Photocell)	M - (Motion Sensor) RC - (Remote Control)

CONTROLS (SOLD SEPARATELY)



P
Photocell



M
Motion Sensor



RC
Remote Controller



GATEWAY

MOUNTING OPTIONS (SOLD SEPARATELY)



N2FWP-NEWSBSF2-D
Slipfitter Mount An optional cast aluminum mast arm adapter secures fixture head to nominal 2"(2-3/8" O.D. pipe size) horizontal steel tenon arm.



N2FWP-NEWSBARM2-D
Arm Mount 4" and 5" Square and Round poles. Standard versatile mounting arm is simple to install and can be used with existing poles for retro installations.



N2FWP-SFARM2-D
SFARM2 Mount An optional cast aluminum mast arm adapter secures fixture head to nominal 2"(2-3/8" O.D. pipe size) horizontal steel tenon arm.



N2FWP-SBT-D
Easy to install for direct wall mounting with 1/2" conduit wiring.




N2FWP-SADP-BAR-D
Square tube light bar installation, with Arm installation of lamps.



N2FWP-ARM-BAR-D
Square tube light bar installation, with Arm installation of lamps.

DIMENSION / EPA DETAILS



A-14.57" x B-25.53" x C-3.16"

	GROSS WEIGHT		23 lbs	BOX DIMENSION		28.74" x 17.32" x 6.1"
CONFIGURATION						
	1	2 @ 180°	2 @ 90°	3 @ 90°	3 @ 120°	4 @ 90°
EPA	0.86 ft ²	1.72 ft ²	1.38 ft ²	2.24 ft ²	2.10 ft ²	2.76 ft ²
NET WEIGHT	21.4 lbs	42.8 lbs	42.8 lbs	64.2 lbs	64.2 lbs	85.6 lbs

ELECTRICAL LOAD




WATTAGE	CURRENT (VOLTAGE) (AMP)					
	120V	208V	240V	277V	347V	480V
N2FWP-SB40W27	3.33 Amp	1.92 Amp	1.66 Amp	1.44 Amp	1.15 Amp	0.83 Amp

Wattage: 400W

DISTRIBUTION (Shown: N2FWP-SB40W27-40K)

TYPE II

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






TYPE II

Type II optics produce a symmetrical pattern that evenly shines light on both sides of the lamp. In a back-to-back configuration, it creates a rectangular pattern.

TYPE III

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






TYPE III

Type III optics produce an asymmetrical pattern that directs the majority of the light forward and equally on both sides of the luminaire. In a back-to-back configuration, it creates a rectangular pattern.

TYPE IV

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM






TYPE IV

Type IV is suitable for applications where light is primarily required forward with minimal backlight. Typical installations include perimeter poles.

TYPE V

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



TYPE V

Type V optics produce a symmetrical square distribution pattern that distributes light equally on all sides of the luminaire. Type 5 luminaires are universal for most area lighting applications.