

SPTMRI

2X2 LED LAY-IN LUMINAIRES



DESCRIPTION: The SPTMRI is a recessed luminaire designed for use in MRI rooms and imaging suites. Sleek design and non-ferrous construction make the fixture safe for use around MRI equipment. Artwork creates a "skylight" effect, which can be soothing for patients.

ELECTRICAL SYSTEM: Long-life LED system rated for >100K hours (L70 @ 45°C). Complies with federal energy efficiency standards. Remote mounted power supply available with up to 8 dimming drivers.


CONSTRUCTION: Non-Ferrous aluminum construction. White powdercoat finish.

ARTWORK: Available in 3 different cloud options, and 3 different space options. Consult factory for additional options.

LISTINGS: NSF2 compliant (Non-Food, Splash Zone). ETL and cETL listed. Made in the USA. FCC Part 15 certified for EMI/RFI emissions.

MOUNTING: Recessed Grid mounting.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty.



The SPTMRI has a unique shroud that gives the effect of a skylight (fixture is shipped assembled)


Ordering Information on Next Page ►

ORDERING INFORMATION Example: SPTMRI-65-40W-L22-S2

SERIES	CCT	OUTPUT	ORIENTATION	LENS OPTIONS
SPTMRI	27 2700k	30W 3750lm	L22 ONE 2'X2' Landscape	OP Opaque Lens
	30 3000k	40W 5000lm	L42 TWO 2'X2's Landscape	C1 Clouds #1
	40 4000K		L44 FOUR 2'X2's Landscape	C2 Clouds #2
	65 6500K		L64 SIX 2'X2's Landscape	C3 Clouds #3
			L66 NINE 2'X2's Landscape	S1 Space #1
			P24 TWO 2'X2' Portrait	S2 Space #2
			P46 SIX 2'X2's Portrait	S3 Space #3
				XX Custom (consult factory)

See last page for
orientation diagrams


See next page for
artwork examples



NEW RF/EMI SOLUTION FOR MRI SUITES AND OUR REMOTE POWER BOX OPTIONS CAN BE FOUND ON PAGES 6-9

Dimensions on Next Page ►


ARTWORK




C1



S1



C2



S2








C3




S3

FIXTURE DIMENSIONS



ORIENTATIONS



ENERGY AND PERFORMANCE DATA

INPUT VOLTAGE:	120/277VAC
POWER CONSUMPTION:	30 OR 40 WATTS*
DELIVERED LUMEN OUTPUT:	3750-5000
STANDARD DIMMING CONTROL:	0-10V
CCT:	6500K
CRI:	82 (MINIMUM)
LIFE TIME RATING:	>120,000 HRS @ L70
INPUT FREQUENCY:	50/60 HZ
POWER FACTOR:	>0.9
OPERATING TEMP:	-30° TO 50° C


*ACTUAL WATTAGE MAY DIFFER BY ±5% WHILE OPERATING 120/277V ±10%

RPB

REMOTE POWER BOX



NEW RF/EMI SOLUTION FOR MRI SUITES



SEE THE FOLLOWING PAGES
FOR OUR NEW MRIFX
RF/EMI FILTER PANEL


Electronic remote power supply provides power from outside the shielded MRI room, within the remote power supply enclosure.

MOUNTING INSTRUCTIONS

1. Mount the remote mounted power supply outside the MRI room.
2. Each driver will have an individual quick-connect for ease of wiring.
3. Ensure that all power/dimming wiring is completely shielded in grounded conduit. Use a minimum of 18 AWG low voltage supply wire.
4. Connect wiring to the driver and run to the installed fixtures. Connect hot and neutral wires to the light fixtures quick connects.
5. Installation is complete.

Ordering Information


SERIES	HOUSING SIZE	# OF DRIVERS	OPTIONS
RPB	6 Fits up to 6 drivers 9 Fits up to 9 drivers	D1 1 LED 1% Dimming Drivers D2 2 LED 1% Dimming Drivers D3 3 LED 1% Dimming Drivers D4 4 LED 1% Dimming Drivers D5 5 LED 1% Dimming Drivers D6 6 LED 1% Dimming Drivers D7 7 LED 1% Dimming Drivers D8 8 LED 1% Dimming Drivers D9 9 LED 1% Dimming Drivers	AM Anti-Microbial White Paint




IMPORTANT: EACH FIXTURE REQUIRES IT'S OWN DRIVER

Dimensions on following page ►

RPB-6




RPB-9



Sample wiring diagrams on following pages ►

MRI ROOM FILTER PANEL

MRIFX




The **MRIFX** is our RF/EMI Power filter solution for MRI suites. With this panel installation of a completed MRI suite is completed in less time and is more organized. This filter panel can be configured with 2 to 32 filters (**each light fixture requires 2 filters**), and installation is easy and straight-forward. This panel is mounted to the wall between the power supplies (see our RPB, next page) and the non-ferrous light fixtures in the MRI suite. The RF/EMI Power Filters available with the MRIFX are some of the highest quality filters available, and are specifically designed to eliminate RF/EMI emissions.

FILTER PANEL: Made from non-ferrous, marine grade aluminum and coated with a premium powder coat, this plate is an integral component designed for many years of use. This plate can accommodate up to 32 RFI filters (for up to 16 light fixtures). A standard DIN rail keeps wiring EMC blocks secure and in place. Custom sized plates are available (consult with factory). The EMC Wiring Blocks (one of each side of panel) are designed to minimize Electromagnetic Interference (EMI) and maintain Electromagnetic Compatibility (EMC).

WIRING: Specially made shielded wiring is utilized to help insure RF/EMI transmissions are negligible.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty.



Ordering Information on Next Page ►



ORDERING INFORMATION Example: MRIFX-04

SERIES	FILTERS
MRIFX	02 Panel with 2 filters for 1 fixture
	04 Panel with 4 filters for 2 fixtures
	06 Panel with 6 filters for 3 fixtures
	08 Panel with 8 filters for 4 fixtures
	10 Panel with 10 filters for 5 fixtures
	12 Panel with 12 filters for 6 fixtures
	14 Panel with 14 filters for 7 fixtures
	16 Panel with 16 filters for 8 fixtures
	18 Panel with 18 filters for 9 fixtures
	20 Panel with 20 filters for 10 fixtures
	22 Panel with 22 filters for 11 fixtures
	24 Panel with 24 filters for 12 fixtures
	26 Panel with 26 filters for 13 fixtures
	28 Panel with 28 filters for 14 fixtures
	30 Panel with 30 filters for 15 fixtures
	32 Panel with 32 filters for 16 fixtures

STAND-ALONE FILTER ORDERING

SERIES	FILTERS
MRIFX	F2 Set of 2 filters for 1 fixture
	F4 Set of 4 filters for 2 fixtures
	F6 Set of 6 filters for 3 fixtures
	F8 Set of 8 filters for 4 fixtures
	F10 Set of 10 filters for 5 fixtures
	F12 Set of 12 filters for 6 fixtures
	F14 Set of 14 filters for 7 fixtures
	F16 Set of 16 filters for 8 fixtures
	F18 Set of 18 filters for 9 fixtures

DIMENSIONS



Dimensions on Next Page