

# X5UBAA

## BAA Compliant LED Exit Sign



### STANDARD



### OPTIONAL



### ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.

### ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### MOUNTING

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

### HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.
- EZ snap-out Chevron directional indicators.
- Compact, low-profile design.


### OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.
- Custom: Signs available with requested 'special' wording.

### WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.

### DIMENSIONS



### ORDERING INFORMATION

Sample Part Number: **X5UBAA2RWEM**

Special voltage & SALIDA face plate options available. Check with your Advantage Representative.

<sup>1</sup> Available only with EM units.

Available only with AC units.

MODEL	No. of FACES	LETTER COLOR	HOUSING COLOR	BATTERY	OPTIONS	
X5UBAA	2	Universal Single/Double Face	R Red	W White	(blank) AC-Only	SDT Self-Diagnostics <sup>1</sup>
			G Green	B Black	EM Battery Backup	2C Dual Circuit Operation <sup>2</sup>
					Custom Custom Wording	
					cUL cUL Listed	

**CUSTOM WORDING SIGN ORDER FORM**



**CUSTOM X5U EXIT TEMPLATE**

**EZ OPTIONS**


- Red Letters
- Green Letters

---

- White Housing
- Black Housing



Sample: Write text in the given area to the right



**ELECTRICAL INFORMATION**

Catalog Number	Input Watts (W)		Input Amps (A)	
	120V	277V	120V	277V
X5U RED/GREEN/EM/2C/SDT	3.8	3.8	0.034	0.020