

VANDAL RESISTANT WET LOCATION

XDLVPWL

4.0" X 4.5" LINEAR SURFACE MOUNT OR PENDANT MOUNTED



The **XDLVPWL** is a vandal resistant LED linear wet location surface mount fixture. Engineered for high abuse areas like sports facilities, transportation venues, public areas, and anywhere that a strong linear fixture is needed.

CONSTRUCTION: Constructed of a precision cut, proprietary aluminum extrusion with flat end caps. Vandal-resistant doorframe prevents fixture abuse and seals the fixture. Available in custom RAL finishes.

DOOR FRAME: Thick aluminum doorframe attaches to housing with tamper-proof Torx head with center pin fasteners. Doorframe seals to housing with gaskets to prevent water and dust from entering the fixture.

MOUNTING: Surface mounting installation is standard, with a special mounting bracket available for quick surface installation. Also available with as pendant mounting. LEDs High Output 80 CRI LEDs are available in 2700K, 3000K, 3500K, 4000K, and 5000K color temperatures. Integral LEDs are rated for at least 100K life hours (L70). 90 CRI available.

OPTIC: Vandal-resistant frosted polycarbonate withstands high abuse, while providing optimal light transmission and LED diffusion.

DRIVER: 0-10V dimming driver included standard. Driver options available for 1% dimming, Lutron EcoSystem, and DALI are available. Finish Matte white finish standard. Custom finish options are available in various RAL colors.

LISTINGS: ETL and cETL listed. RoHS compliant. Suitable for wet locations under covered areas. Manufactured in the USA, BAA compliant.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty

Ordering Information and Dimensions on Next Page ►

ORDERING INFORMATION

Example: XDLVPWL-40-20L-VRFP-M-4

SERIES	CCT	OUTPUT	LENS	FINISH	LENGTH	DRIVER
XDLVPWL	27 2700K	5L 500 lm/ft.	VRFP Vandal Resistant	MW Matte White	2 2 ft	(BLANK) 0-10V 10% dimming driver
	30 3000K	7L 700 lm/ft.	Frosted	Finish	3 3 ft.	CD1 0-10V 1% dimming driver
	35 3500K	10L 1000 lm/ft.	Polycarbonate (.125P)	UB Urban Bronze	4 4 ft.	CD5 0-10V 5% dimming driver
	40 4000K	14L 1400 lm/ft.	125P .125 Clear Polycarbonate	SP Special Finish	5 5 ft.	EDN Non-dimming electronic driver
	50 5000K	XXXL Custom lm/ft.	250P .250 Clear Polycarbonate		6 6 ft.	DALI DALI 1% dimming driver
					7 7ft.	LDE1 Lutron Hi-Lume 1% EcoSystem LED Driver
					8 8 ft.	
					XX Custom fit.	

VOLTAGE	OPTIONS
M Multi-Volt (120-277VAC)	14EBL 14W Emergency Driver
	SMB Special Surface Mounting Bracket
	90 90 CRI
	10CWEBL 10W Cold Weather Emergency Driver
	1P Single Pendant w/ Reinforcement Plate (Pendant Supplied by Others)
	2P Double Pendant w/ Reinforcement Plate (Pendant Supplier by Others)
RGBW	Addressable DMX Decoder for DMX512 Control (Controller Supplied by Others). Consult factory for requirements.

