

XEMPLPWL LOW-PROFILE WET LOCATION EXIT & EMERGENCY COMBO



The **XEMPLPWL** is a low profile (under 2.5") exit and emergency combo with an impressive set of features. Impact resistant polycarbonate body, WET LOCATION rated, standard emergency battery - plus optional tamper proof fasteners and a cold weather version is just a few features.

ILLUMINATION: Long lasting, efficient, ultra bright white LED lamp heads rated at 1.0W (1 LEDs x 1.0 watt) per head. Adjustable LED lamp heads provide up to 18-ft center-to-center spacing with 3-ft path of egress at 7.5-ft mounting height. Long-life, energy efficient Red or Green LED EXIT sign illumination.

ELECTRICAL: Dual 120/277 voltage. Unique LED indicator light alerts occupant on battery condition (Red-normal, Off-check battery). 3.6V long life, maintenance free, rechargeable NiCd battery. Internal solid-state transfer switch automatically connects the internal battery to LED board and lamp heads for minimum 90-minute emergency illumination. Fully automatic solid state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.

HOUSING: 5VA flame retardant, UV stabilized polycarbonate in white, black or gray finish. High-impact resistant, UV stabilized polycarbonate clear lens. Corrosion resistant enclosure with engineering grade silicone gasket. Knockouts provided for conduit feed applications. EZ snap-out Chevron directional indicators.

MOUNTING: Polycarbonate mounting canopy included for top or end mount. Universal K/O pattern on back plate for wall mount.

OPTIONS: CW: Optional high capacity battery for extreme cold temperature applications (-20°C – 50°C). RC: Remote capacity of up to 2.0 watts. TP: Tamper-proof hardware helps prevent unauthorized access to the unit.

LISTINGS: Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL listed for wet locations (0°C – 50°C). Certified to CEC under Title 20 Regulations.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty.

ORDERING INFORMATION

Example: XEMPLPWL-2-RG-W-CW

SERIES	# OF FACES	LETTER COLOR	HOUSING COLOR	OPTIONS
XEMPLPWL	1 Single Face 2 Double Face Blank Universal Single/Double Face	RG Red/Green (Field Selectable)	W White B Black G Gray (with white faceplate)	CW Cold Weather ¹ RC Remote Capacity ¹ TP Tamper Proof Screws

¹, Not available together

DIMENSIONS

