

XEMNY

NEW YORK CITY APPROVED STEEL LED EXIT SIGN

Ligature-Resistant

*Top Mount Only



Our **XEMNY** is a prison grade LED exit sign with New York compliant **8" TALL EXIT** letters. Perfect for any application that requires a heavy duty, vandal resistant exit sign. Available as top or side mount. This is a clean and attractive exit sign designed to last. Comes standard with a .125" clear polycarbonate lens sealed to the doorframe. Top mount is ligature-resistant when mounted with pick-proof caulk.

ELECTRICAL: 624nm Red or 527nm Green LED light source. Electrical components mounted to removable high impact, injection molded polycarbonate chassis.

LISTINGS: ETL and cETL listed. Meets IK10 requirement, higher ratings available, consult factory. Meets or exceeds UL924 and NFPA 101 Standards. Meets or exceeds CSA and NRCAN requirements.

FASTENERS: T25 Torx with center pin reject is standard.

HOUSING: One-piece die-formed prime 14-gauge grade material as specified – see ordering information. Corners continuously seam welded and smooth.

DOOR: One-piece die-formed prime grade 14-gauge. Corners continuously seam welded and smooth.

FINISH: TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. See Options for black exterior.

OPTIONS: Sealed emergency battery pack with standard deep cycle battery conditioning (provides 90 minutes of emergency operation), plus self test and self diagnostic circuitry available. This exit sign is available as wet location (IP65). The emergency battery pack is suitable for 10°C to 45°C (50°F to 113°F), and a cold weather battery option is available.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at: www.aelnow.com/warranty.

Field Knock-out Chevrons (2)

SIDE
MOUNT



Ordering Information on Next Page ►

ORDERING INFORMATION EXAMPLE: **XEMNY-2-B16-G-R-W-MB-T-M**

SERIES	FACE	HOUSING / DOOR MATERIAL	LEGEND COLOR	EXIT INSERT COLOR	HOUSING COLOR
XEMNY	1 Single Face	B12 Cold Roll 12 Gauge Steel (Painted)	G Green	W White (standard)	MB Matte Black
	2 Double Face	B14 Cold Roll 14 Gauge Steel (Painted)	R Red	B Black	MW Matte White
		B16 Cold Roll 16 Gauge Steel (Painted)			
		B18 Cold Roll 18 Gauge Steel (Painted)			
		SH14 Stainless Steel 14 Gauge (Painted)			
		SH14B Stainless Steel 14 Gauge (Brushed)			
		SH16 Stainless Steel 16 Gauge (Painted)			
		SH16B Stainless Steel 16 Gauge (Brushed)			
		SH18 Stainless Steel 18 Gauge (Painted)			
		SH18B Stainless Steel 18 Gauge (Brushed)			

MOUNTING TYPE		VOLTAGE		OPTIONS	
T	Top Mount	M	120/277VAC	BLANK	AC Only
S	Side Mount*			EM	90 Minute Standard Emergency Backup
				CLD	Cold weather battery
				WL	Wet Location (IP65)
				BLK	Black Exterior (N/A with brushed housing/ door material)
				TS	Torx Screwdriver
				SDT	Self Diagnostic
*NOT Ligature-resistant					

	INPUT WATTS (W)		INPUT AMPS (A)	
	120V	277V	120V	277V
XEMNY	5.0	5.0	0.041	0.018

Dimensions on Next Page 

