

ALLS

NARROW BODY STRIP



DESCRIPTION: Extremely LOW PROFILE T8 (OR T5) SURFACE MOUNT STRIP for use with either remote ballasts or modern LED T8 lamps. Each fixture comes with an integral flex feed adapter. Easy mounting through provided holes in housing. Consult factory for optional reflectors and tandem configurations.

APPLICATIONS: Anywhere an ultra low profile light is required.

CONSTRUCTION: Housing is die-formed and embossed code 22 gauge steel. Finish is high reflectance baked white enamel. Installed end feed connector accepts 3/8" steel flex conduit (available separately).

MOUNTING: Units are easy to install and are pre-wired with 12' leads for instant start ballast.

LISTINGS: ETL and cETL Listed.

WARRANTY: 5 Year Limited Warranty on housing and electronics. Complete warranty and terms located at: www.aelnow.com/warranty.



SIZE W x L x H in inches (mm)

- 2' 1.38" x 25.5" x 1.69"
- 3' 1.38" x 37.5" x 1.69"
- 4' 1.38" x 49.5" x 1.69"
- 6' 1.38" x 73.0" x 1.69"
- 8' 1.38" x 97.0" x 1.69"

ORDERING INFORMATION | Example: ALLS-3-25T8-AC10

| SERIES | SIZE | LAMP TYPE | OPTIONS |
|----------------|------|-------------------------|--|
| ALLS | 2' | 17T8 2 ft. | 14EBLT 14 Watt Emergency Ballast (remote mount only) |
| | 3' | 25T8 3ft or 6ft Tandem | |
| ALLST (tandem) | 4' | 32T8 4ft or 8 ft Tandem | AC10 Aircraft Cable 10' |
| | 6' | 24T5 2 ft. | AC20 Aircraft Cable 20' |
| | 8' | 35T5 3ft or 6ft Tandem | |
| | | 54T5 4dt or 8ft Tandem | |