



BAQ Wall/Surface LED Prison Grade



WALL MOUNT
SURFACE MOUNT
Wet Location
IP64

HOUSING

The BAQ is built from 16 gauge stainless steel post painted electrostatically applied white TGIC polyester powder coat – 5-stage pre-treatment. Integral heat sinks. Housing flange interlocks and wraps around lens base producing maximum moisture deflection and resistance to prying. Housing provided with four standoff mounting holes, one 3/4" tapped hole on back of housing, four 3/4" tapped and plugged holes on sides of housing.

ELECTRICAL SYSTEM

Electronic, standard 0-10V, dimming.

OPTICAL SYSTEM

UV-stabilized, high impact resistant, virgin injection molded polycarbonate. Lens secured with four concealed captive Torx screws with center pin. High impact resistant.

LISTINGS

IP64

UL listed for damp location. Wet locations available.

LED

80 CRI or 90 CRI LEDs available in 2700K, 3000K, 3500K, 4000K and 5000K. Life is 100,000 hours at 70% lumen maintenance.

DOORFRAME GASKET

Die-cut, closed cell EPDM self adhesive gasket seals housing to mounting surface. Closed cell, silicone "O" ring gaskets positioned and friction secured in gasket channels of lens base and housing.

WARRANTY

5 - Year Limited Warranty. Complete warranty and terms located at: www.aelnow.com/warranty

STANDARD



OPTIONAL



PART#	DELIVERED LUMENS	WATTS	L70 @20C (HRS)
2L	2000 LUMENS	14.1	>100K
3L	3000 LUMENS	21.2	>100K
5L	5000 LUMENS	35.2	>100K
6L	6000 LUMENS	42.3	>100K

ORDERING INFORMATION

Example: BAQ-40-3L-M-W

SERIES	COLOR TEMP	ILLUMINATION LEVEL	VOLTAGE	FINISH	OPTIONS
BAQ	Full Face	27 2700K	M 120/277V	BR Dark Bronze	12EBL 1200 Lumen Emergency Ballast
		30 3000K		G Forest Green	FZ Fuse Holder
		35 3500K		LG Light Gray	NAT Natatorium Rated
		40 4000K		MB Matte Black	OC4EX Occupancy Sensor
		50 5000K		MW Matte White	WL Wet Location
		2L 4500 Lumens		S Silver	
		3L 3000 Lumens		CC Custom Color	
		5L 5000 Lumens			
		6L 6000 Lumens			

FIXTURE DIMENSIONS

