


CE Series

LED Back-lit Flat Panel
 20" X 48"



PRODUCT SPECIFICATIONS

DESCRIPTION

The CE Series is a 20"x48" back-lit flat panel. Back-lit design provides even illumination.

APPLICATIONS

The CE Series of LED Flat Panels were designed for areas requiring a 20"x48" custom sized flat panel. Applications include commercial applications, offices, government facilities, schools, public areas and more.

CONSTRUCTION

The fixture is constructed of a heavy gauge frame. Housing embossed for maximum rigidity. Rounded side flanges for safe handling.

OPTICAL SYSTEM

Back-lit LED system provides for even and glare-free illumination. White polyester polymer finish with a minimum 82% reflectivity.

ELECTRICAL SYSTEM

0-10V dimming standard, 120/277V applications. Long-life LED system rated for >50K life hours (L70 @ 25°C) with a CRI >80. Complies with federal energy efficiency standards.

MOUNTING

The fixture is designed for recessed applications, with surface mount and flange kits available.

LISTINGS

UL and cUL Listed. Independently tested to IESNA LM-79 and LM-80 specifications. Damp location rated.


WARRANTY

5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty

ORDERING INFORMATION

Example: CE20X4840SM

SERIES	SIZE	CCT	OUTPUT	VOLTAGE	OPTIONS
CE	20X48 20"x48"	30 3000K	S Standard	M Multi-Volt (120-277 VAC)	12EBL 12W Emergency Driver
		35 3500K	M U		FW 6' Flex Whip
		40 4000K	H = h		C6SJ 6' SJ Flex Whip 16/3
		50 5000K			C10SJ 10' SJ Flex Whip 16/3
					AC20 20' Aircraft Cable
					FK20X48 Flange Kit
					SMS20X48 Surface Mount Shroud

FIXTURE DIMENSIONS

ILLUMINATION PACKAGES

Output	Delivered Lumens	System Wattage	L70 @ 25°C (hrs)
S	3000	24	>50K
M	4500	36	>50K
H	6000	48	>50K

* Delivered Lumens shown were tested with 4000K LEDs