

# CLQ

Back Lit ISO 5 Clean Room  
 Static White Flat Panel



### PRODUCT FEATURES

#### DESCRIPTION

The CLQ is an economical clean room flat panel suitable for ISO class 5-9 positive pressure clean rooms. Static white CCT, available in 3000K, 4000K, or 5000K. No flickering, even and soft illumination with uniform light.

#### CONSTRUCTION

Constructed of a heavy gauge aluminum frame with high heat dissipation. Zero distance between the back cover and the frame to eliminate particle transfer.

#### OPTICAL SYSTEM

Lens is optimized to protect against yellowing and light degradation. Provides even and soft, uniform illumination.

#### ELECTRICAL SYSTEM

0-10V dimming standard. >50,000 hour LEDs at L70 for reduced maintenance, LEDs available in 3000K, 4000K, or 5000K color temperatures.

Operating temperatures: -10°C to 40°C (14°F to 104°F)

#### MOUNTING

The fixture is designed to be recess mounted in grid ceiling systems.

#### LISTINGS

UL listed for damp locations. LM79, LM80 and TM21 compliant. Tested in accordance with ISO 14644-1; suitable for ISO Class 5-9 positive pressure cleanrooms. NSF Listed.

#### WARRANTY

5-Year Limited Warranty. Complete warranty and terms located at [www.aelnow.com/warranty](http://www.aelnow.com/warranty). 10-Year warranty optional

## ORDERING INFORMATION

Example: CLQ24-40-S-M


SERIES	CCT	OUTPUT	VOLTAGE	OPTIONS
CLQ24 1x4	30 3000K	L 50W (5250lm)	M 120/277 (Multi-volt)	EM 8W Emergency
	40 4000K	S 72W (7560lm)		10YR 10-Year Warranty
	50 5000K			

## LED SYSTEM INFORMATION

Output	Delivered Lumens	Luminous Efficacy	L70 @45°C (hrs)
L (50W)	5250	105 lm/W	>50K
S (72W)	7560	105 lm/W	>50K

**PRODUCT DIMENSIONS**

front view



side view

