ADVANTAGE ENVIRONMENTAL LIGHTING

CATALOG #:	
PROJECT:	
TYPE:	

HWP

Wattages: 50W, 70W, 100W
Tunable Wattages: 30W/50W/60W/70W

Glass Wall Pack Series

LED Semi Cut-Off Wall Pack series can be widely used in indoor or outdoor lighting (wet location). Ideal for mechanical or electronic processing workshops, storage warehouses, steel mills, gas stations, toll booth, waiting rooms, the platforms of railway station, indoor stadiums.

WATT/CCT
FIELD-ADJUSTABLE

FEATURES

- Lumileds LED, high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V/AC 277-480V.
- Excellent optics design, greatly improve the light utilization and evenness.
- Motion sensor control available (Optional)
- 1-10V Dimming.

Die-cast aluminum cooling design, high quality and better cooling for LED Tj < 85°C.

ORDERING INFORMATION

EXAMPLE:
HWP-07W-27-50K-P

PRODUCT	WATTAGE	VOLTAGE	CCT	FINISH	CONTROL
HWP Semi Cut-Off Wall Pack	***45W -** (45W) **07W -** (70W) **10W -** (100W) **12W -** (120W)	**27** (AC120-277V) ***347** (AC347V) **48** (AC277-480V)	**40K -** (4000K) **50K -** (5000K)	**D** - (Dark Bronze) **W** - (White) **B** - (Black) **S** - (Silver)	**P -** (Photocell)

ADVANTAGE ENVIRONMENTAL LIGHTING

CATALOG #:

PROJECT:

TYPE:

CONTROLS (SOLD SEPARATELY)

P (Photocell)

WATT/CCT FIELD-ADJUSTABLE

EMERGENCY BACK-UP (SOLD SEPARATELY)

BLD-CM20N-480800-8W
8W Emergency Backup Battery
LED Driver

BLD-CM20N-480800-15W
15W Emergency Backup Battery
LED Driver

BLD-CM20N-480800-20W
20W Emergency Backup Battery
LED Driver

SPECIFICATION					
WATTAGE	45W	70W	100W	120W	30W/45W/60W/70W
LUMEN	6651 lm	10150 lm	14300 lm	17035 lm	4483 / 5896 / 7636 / 8776 lm
EFFICACY	147 lm/W	145 lm/W	143 lm/W	141 lm/W	up to 125 lm/W
CCT	4000K, 5000K				3000K/4000K/5000K
CRI	70				70
INPUT VOLTAGE	120-277V / 347V	120-277V / 277-480V			120-277V
POWER FACTOR	0.95				0.95
DRIVER EFFICACY	90%				90%
DIMMING	1-10V Dimming				1-10V Dimming
LIGHT ANGLE	97.1° X 70°	96.3° X 71°	136.8° X 74.8°	148° X 77.3°	97°X70°
LIFE SPAN	75,000 hrs				
WORKING TEMPERATURE	-22°F ~ 113°F				
STORAGE TEMPERATURE	-40°F ~ 176°F				
OUTDOOR RATING	Wet Location / IP66 Rating				
CABLE	Input Connect, No cable				
WARRANTY	5 year limited				

ADVANTAGE ENVIRONMENTAL LIGHTING

CATALOG #:	
PROJECT:	
TYPE:	

DIMENSION

WATTAGE	**45W**
NT. WEIGHT	6.6 lbs/carton
BOX DIM.	15.5” x 8.85” x 8”

WATTAGE	**70W**
NT. WEIGHT	7.7 lbs/carton
BOX DIM.	15.5” x 10.23” x 8.6”

WATTAGE	**100W / 120W**
NT. WEIGHT	9.1 lbs/carton
BOX DIM.	16” x 9.25” x 9.25”

WATTAGE	**34567W**
NT. WEIGHT	6.88 lbs/carton
BOX DIM.	15.5” x 8.07” x 7”