ADVANTAGE ENVIRONMENTAL LIGHTING

MADE IN THE USA

CATALOG #:

PROJECT:

TYPE:

LDL6WS 6" X 6" WALL MOUNT INDIRECT STEEL LINEAR LUMINAIRE

DESCRIPTION: The LDL6WS is an architecturally designed Wall Mount Direct Steel LED Luminaire that is classically styled and fit for any interior. It is available for continuous run mounting..

APPLICATIONS: The LDL6WS LED Luminaires are designed to be high quality, energy efficient fixtures for use in commercial applications, offices, hotel lobbies, museums, government facilities, schools, and public areas.

CONSTRUCTION: The fixture is constructed of a 6" wide heavy gauge steel body. The LDL6WS is available in any run length withing 1' increments. Heavy duty housing crimped along sides for extra rigidity and straight alignment.

OPTICAL SYSTEM: High output LED's available in 3000K, 3500K, 4000K, and 5000K. CRI >82 (90 CRI is available). Satin lens provides for a beautiful architectural design while maintaining optimal light output.

ELECTRICAL SYSTEM: Electronic drivers are available for 120/277V applications. >100K life hours (L70 @ 25°C). Metal gear tray for internal LED driver. Complies with federal energy efficiency standards.

MOUNTING: This fixture is designed to be wall mounted. Continuous run available.

LISTINGS: ETL and cETL listed. RoHS compliant. Suitable for wet locations (IP65).

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at **www.aelnow.com/warranty**. 10 year warranty available as an option below.

Ordering Information on Next Page

ADVANTAGE ENVIRONMENTAL LIGHTING

CATALOG #:

PROJECT:

TYPE:

ORDERING INFORMATION. Example: LDL6WIS-4-40-12L-M-S-W

SERIES	LENGTH		CCT		OUTPUT		VOLTAGE		LENS		FINISH		OPTIONS	
LDL6WIS	2	2 ft.	30	3000K	5L	500 lm/ft	M	Multi-Volt (120-277V)	S	Satin Acrylic	W	Matte White	14EBL	14 Watt Emergency Ballast
	3	3 ft.	35	3500K	7L	700 lm/ft					SP	Special Finish	FW	Flex Whip Cable 6'
	4	4 ft.	40	4000K	10L	1000 lm/ft								
	5	5 ft.	50	5000K	14L	1400 lm/ft								
	6	6 ft.			XXXL	XXX lm/ft								
	7	7 ft.												
	8	8 ft.												
	XX	XX ft.												

FIXTURE DIMENSIONS

For Continuous Run Mounts:

LED Information

OUTPUT	5L	7L	10L	14L
Lumens	500	700	1000	1400
System Wattage/Ft.	3.125W	4.375W	6.25W	8.75W
Efficacy (Lm/W)	160	160	160	160
CRI	>82	>82	>82	>82
Dimming	0-10V	0-10V	0-10V	0-10V
Color Consistency	>3 SDCM	>3 SDCM	>3 SDCM	>3 SDCM
Rated Life (L70)	>100,000 hrs.	>100,000 hrs.	>100,000 hrs.	>100,000 hrs.

Lumens calculated with 4000K CCT LEDs