



LSSLOT 2.5" RECESSED
VANDAL RESISTANT
RGBW OR STATIC



Anti-Ligature



Our LSSLOT is a flexible LUMINAIRE that features a shallow housing that is vandal and ligature resistant. Perfect for uses in hospitals, behavioral health facilities, education, transportation, and any where a secure light is needed.

HOUSING AND LENS: Shallow extruded aluminum housing with vandal and ligature resistant frame. Ligature resistant smooth single piece aluminum frame with 0.22" polycarbonate lens

FASTENERS: Discreet tamper-proof fasteners placed along edge of frame to fixture housing.

OPTICAL SYSTEM: High output LED's available in 3000K, 3500K, 4000K, and 5000K, or choose the RGBW option.

LIGATURE RESISTANCE: Provides ligature resistance when installed in sheetrock/ drywall WHEN utilizing a tamperproof security sealant/pickproof security caulk (supplied by others).

ELECTRICAL SYSTEM: Indoor/Outdoor: -30°C to 60°C (-22°F to 140°F). 0-10V 1.0% dimming standard.

MOUNTING: This fixture is designed for recessed mounting.

LISTINGS: IK10-Rated, ETL rated, and LM-80 Qualified, LM-79 Certified.

RGBW OPTION: Anti-pixelation optical film included above polycarbonate lens. Quad chip RGBW LEDs provide rich color palette for full spectrum expression.

WARRANTY: 5-Year Limited Warranty. Complete warranty and terms located at www.aelnow.com/warranty.

ORDERING INFORMATION ON NEXT PAGE ►

ORDERING INFORMATION:

Example: LSSLOT-

SERIES	LINEAR	CCT	OUTPUT	MOUNTING	VOLTAGE	FINISH	APPLICATION
LSSLOT	2 2 ft. 4 4 ft. 6 6 ft. XX XX ft.	30 3000K 35 3500K 40 4000K 50 5000K	5L 500 lm/ft 7L 700 lm/ft 10L 1000 lm/ft 14L 1400 lm/ft XXXL XXX lm/ft	L Lay-in Grid F Flanged FT Flangeless Trim (Compatible with GYP ceiling)	M Multi-Volt (120-277V)	W Matte White SP Special Finish	XX FTW Length in Feet (Wall) XX FTC Length in Feet (Ceiling) A 1'x1' "L" section is used as a joiner, so take that dimension into account when ordering.

Lumens shown based on 4000K CCT. Consult factory for other options.

OPTIONS

14EBL	14 Watt Emergency Ballast
EC	Emergency Circuit
90	90 CRI
L	90 Degree Ceiling-to-Wall
XXV	XX Degree Ceiling-to-Wall
AM	Anti-Microbial White Paint
DMX	Addressable DMX Decoder for DMX512 Control (Controller Supplied by Others). Consult factory for requirements.

