



CATALOG #:

PROJECT:

TYPE:

# LVT120

## COMMERCIAL GRADE LED VAPOR TIGHT



**DESCRIPTION:** The LVT Series is a Commercial Grade LED Vapor Tight, gasketed enclosure that is completely dust and moisture resistant. The LVT utilizes state-of-the-art LED technology to deliver the highest possible efficiency in the lighting industry and is utilizes JA8 compliant boards.

**APPLICATIONS:** The LVT Series of LED Vapor Tights were designed to be high quality, energy efficient LED fixtures for use in food processing facilities, kitchens, parking garages, canopy, stair well car washes, government facilities, schools, public areas and industrial facilities. Suitable for both indoor and outdoor applications.

**CONSTRUCTION:** The fixture is constructed of a fiberglass housing with a VA (f1) FRP UL rating, and an acrylic or polycarbonate diffuser securely positioned in a permanent, poured-in-place, polyurethane sealing gasket. The diffuser and upper components are locked in place and sealed tightly with polycarbonate retaining latches or optional stainless steel latches. High impact acrylic/DR material diffuser composition. Positive cam latches. Polyethylene molded end plugs.

**OPTICAL SYSTEM:** High output LED's available in 2700K, 3000K, 3500K, 4000K, and 5000K. CRI >82. Diffuser softens light dissipation for even light coverage. Various lens materials available.

**ELECTRICAL SYSTEM:** 0-10V dimming driver included standard. Long-life LED system rated for >120K life hours (L70 @ 25°C). Metal gear tray for internal LED driver. Complies with federal energy efficiency standards.

**CONTROLS:** The fixture is compatible with 0-10V dimming controls, 0-10V dimming driver included standard. 50% step dimming is available upon request.

**MOUNTING:** The fixture can be suspended or surface mounted. Optional top only hub entry or combination top and end hub entry available for stem mounting applications. Die formed galvanized mounting brackets come standard. No holes required for mounting. Unitized internal/external brass mounting stud for structural integrity and continuity of ground.

**LISTINGS:** Independently tested to IESNA LM-79 and LM-80 specifications. UL and cUL Listed. CSA approved. NSF International Certified. IP65, IP66 and IP67 Certified for Wet Location applications. Proudly made in America. Manufactured in Fort Worth, Texas.

**WARRANTY:** 5-Year Limited Warranty. Complete warranty and terms located at [www.aelnow.com/warranty](http://www.aelnow.com/warranty).

### ORDERING INFORMATION

Example: LVT-2-30-5L-M-SA-OC4EX-TR120D


SERIES	LENGTH	CCT	OUTPUT	WATTAGE	LENS OPTIONS	OPTIONS		
LVT	2	27.69" Overall	27	2700K	120 120VAC	BLANK Shallow Lens Acrylic Frosted) - Standard RA Acrylic Ribbed RB Acrylic Ribbed* (Frosted) DAF Deep Lens Acrylic* (Frosted) DAS Deep Lens Acrylic* (Smooth) SA Shallow Lens Acrylic* (Smooth) SPF Shallow Lens Polycarbonate* (Frosted) SPS Shallow Lens Polycarbonate* (Smooth)	12EBL 1200 Lumen Emergency Ballast	
		30	3000K	2L 2000 Lumens			OC4EX Occupancy Sensor	
	4	51.65" Overall	35	3500K			3L 3000 Lumens	1P Single Pendant w/ Reinforcement Plate (Pendant Supplied by Others)
		40	4000K	5L 5000 Lumens			2F Double Pendant w/ Reinforcement Plate (Pendant Supplier by Others)	
	8	99.65" Overall	50	5000K			7L 7000 Lumens	SSL Stainless Steel Latches
				10L 10,000 Lumens			SSLTP Stainless Steel Latches Tamper Proof	
				14L 12,000 Lumens			PTP Polycarbonate Tamper Proof Latches	
				18L 18,000 Lumens			LDE1 Lutron LDE1 Hi-Lume 1% EcoSystem Fade-To-Black Driver Upgrade	
				25K 25,000 Lumens			LDE5 Lutron LDE5 5-Series EcoSystem 5% Dimming Driver Upgrade	
				XXXL Custom Lumens			SB Bail Clip (316 Stainless Steel)	
					45WMB 45" Wall Mount Bracket (316 Stainless Steel)			
					90 90 CRI			
					TR120D 120v 2 wire Triac Dimming			

Delivered lumens vary based on length of unit. Consult factory for more info.

\*Additional costs for lens enclosure upgrades

## LVT120

COMMERCIAL GRADE  
LED VAPOR TIGHT




### FIXTURE ANALYSIS

**DIMENSIONS:** 51.65" X 6.77" X 4.25"  
**MOUNTING:** SURFACE OR SUSPENSION  
**WEIGHT:** 12 LBS  
**WARRANTY:** 5-YEAR LIMITED

### LENS DIMENSIONS

**STANDARD:** 1.92" X 6.40"  
**DEEP:** 3.50" X 6.40"  
**SHALLOW:** 1.92" X 6.40"



### ENERGY AND PERFORMANCE DATA

INPUT VOLTAGE:	120/277VAC
SYSTEM INPUT POWER:	13 - 157 WATTS*
DELIVERED LUMEN OUTPUT:	2000 - 25000 LUMENS
STANDARD DIMMING CONTROL:	0-10V
CCT:	3000, 3500, 4000, 5000 KELVIN
CRI:	82 (MINIMUM)
LIFE TIME RATING:	>120,000 HRS @ L70
INPUT FREQUENCY:	50/60 HZ
POWER FACTOR:	>0.9
OPERATING TEMP:	-30° TO 50° C

\*ACTUAL WATTAGE MAY DIFFER BY ±5% WHILE OPERATING 120/277V ±10%

### LED OUTPUT

2L	2000 LUMENS	13	>120K
3L	3000 LUMENS	19	>120K
5L	5000 LUMENS	31	>120K
7L	7000 LUMENS	44	>120K
10L	10,000 LUMENS	63	>120K
14L	12,000 LUMENS	75	>120K
18L	18,000 LUMENS	113	>120K
25K	25,000 LUMENS	157	>120K

Delivered lumens vary based on length of unit.  
Consult factory for more info.