Advantage Environmental Lighting

CATALOG NUMBER	
PROJECT	
TYPE	

VPC & VPW

LED Vapor Tight Jelly Jar



PRODUCT SPECIFICATIONS

DESCRIPTION

The VPC & VPW Series are LED Vapor Tight Jelly Jars, designed to illuminate doorways, scaffolding, parking lots, warehouses, farms, residential areas, walkways, underpasses, gas stations, factories, loading docks and so on. IP65 rated to resist dust, pressurized water, and harsh environments.

- Die-cast aluminum housing
- Input voltage: 120-277V
- High efficacy LEDs, >90 lm/W
- High-temperature silicone gasket protects against moisture and dust
- Frosted glass diffuser provides glare-free light
- >80 CRI
- Operating temperature: -4˚F - 122˚F
- Available in Wall or Ceiling mount
- Four 1/2" conduit entries for easy wiring
- 5 Year Warranty
- Energy Star Qualified
- >50,000 life hours

ORDERING INFORMATION

Example: VPC-20-30-M-17

Series	Wattage	Color Temperature	Driver	Lumens
VPC	20 - 20 Watts	30K - 3000K	M - 120-277V	17 - 1713 Lumens
VPC	20 - 20 Watts	40K - 4000K	M - 120-277V	17 - 1713 Lumens
VPW	20 - 20 Watts	30K - 3000K	M - 120-277V	17 - 1713 Lumens
VPW	20 - 20 Watts	40K - 4000K	M - 120-277V	17 - 1713 Lumens

DIMENSIONS