ADVANTAGE
ENVIRONMENTAL LIGHTING

X17BA

DIE-CAST ALUMINUM EXIT SIGN

The **XALUM** series is an ultra-bright, energy efficient, long-life Red or Green LED aluminum body exit sign. Available as single or double face, and can be installed as either top or end mount.

APPLICATIONS: Our XALUM is designed to be used within a very wide area of applications. Options such as tamper proof fasteners, dual circuit power and internal emergency battery further extend this exit signs appplication ability.

CONSTRUCTION: Premium-grade, die-cast aluminum housing. Unique design allows double face conversion in the field. Quick-snap face plate closure. Includes Field selectable knockout Chevron directional indicators.

OPTICAL SYSTEM: The LSR comes standard with a round frost white lens.

ELECTRICAL SYSTEM: Dual 120/277 voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 4.8V long life maintenance-free, rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING: This fixture is designed to surface or suspension mounted. Aluminum mounting canopy included for top or end mount. Universal K/O pattern on back plate for wall mount.

LISTINGS: Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. UL Listed for damp locations (0°C – 50°C). Certified to CEC under Title 20 Regulations.

ORDERING INFORMATION.   Example: XALUM-2-R-A-A-EM

SERIES	# OF FACES		LETTER COLOR		HOUSING		FACE		BEAM ANGLE		GLASS TYPE	
XALUM	1	Single Face	R	Red	W	White	W	White	(blank)	AC-Only	SDT	Self-Diagnostics(1)
	2	Double Face	G	Green	B	Black	B	Black	EM	Battery backup	2C	Dual Circuit Operation(2)
	3	Universal Single /Double Face			A	Aluminum	A	Aluminum			TP	Tamper-Proof

(1) Available only with EM units. (2) Available only with AC units.

8 3/8"

12 5/8"

1 7/8"