



## X17BAA

### Die-Cast Aluminum Exit Sign

STANDARD



OPTIONAL



#### ILLUMINATION

- Ultra bright, energy efficient, long life Red or Green LEDs.

#### ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

#### MOUNTING

- Aluminum mounting canopy included for top or end mount.

#### HOUSING

- Premium-grade, die-cast aluminum housing.
- Field selectable knockout Chevron directional indicators.
- Unique design allows double face conversion in the field.
- Quick-snap face plate closure.


#### OPTIONS

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time.
- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

#### WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C – 50°C).
- Certified to CEC under Title 20 Regulations.

#### DIMENSIONS



#### ORDERING INFORMATION

Sample Part Number: X17BAA 1RBAEM

Special voltage options available. Check with your Advantage Representative.

MODEL	No. of FACES	LETTER COLOR	HOUSING COLOR	FACE PANEL	BATTERY	OPTIONS
X17BAA	1	Single Face	R Red	A Aluminum	A Aluminum	(blank) AC-Only
			G Green			EM Battery Backup
						SDT Self-Diagnostics <sup>1</sup>
						2C Dual Circuit Operation <sup>2</sup>
						TP Tamper-Proof

<sup>1</sup> Available only with EM units.

<sup>2</sup> Available only with AC units.